





# THREAD ROLLING SCREWS



## GENUINE TAPTITE II

®Taptite is a registered trademark of REMINC (Research Engineering & Manufacturing Inc.)

		C		D		G	Thread Length	Torsional Strength		
Size of Screw		Diameter of Circumscribing Circle		Measurement Across Center		Dia. of Circum. Circle		Screw Lengths as Listed & Shorter Thread to Head	(Free breaking Torque of screw)	
Inch Nominal Screw Size Dia.-T.P.I.	MM Nominal Screw Pitch Dia.-Pitch	Maximum	Minimum	Maximum	Minimum	Maximum	Minimum		lb.In.	Nm.
		In.	In.	In.	In.	In.				
2-56	2.5-0.45	.0875	.0835	.0840	.0800	.070	5/8	6	--	
3-48	2.5-0.53	.1010	.0970	.0970	.0930	.081	5/8	10	-	
4-40	2.8-0.64	.1145	.1105	.1095	.1055	.090	3/4	14	2.71	
5-40	3.2-0.64	.1275	.1235	.1225	.1185	.103	7/8	22		
6-32	3.5-0.79	.1410	.1350	.1350	.1290	.111	7/8	24		
8-32	4.2-0.79	.1670	.1610	.1610	.1550	.137	1	48	5.40	
10-24	4.8-1.06	.1940	.1880	.1850	.1790	.153	1 1/4	65	7.34	
10-32	4.8-0.79	.1930	.1870	.1870	.1810	.163	1 1/4	81	9.15	
12-24	5.5-1.06	.2200	.2140	.2110	.2050	.179	1 3/8	105	11.90	
1/4-20	6.3-1.27	.2550	.2490	.2460	.2400	.206	1 1/2	160	18.10	
5/16-18	7.9-1.41	.3180	.3120	.3080	.3020	.264	1 1/2	340	38.40	
3/8-16	9.5-1.59	.3810	.3750	.3710	.3650	.320	1 1/2	620	70.00	
7/16-14	11.1-1.81	.4445	.4385	.4315	.4255	.375	1 1/2	950	107.33	
1/2-13	12.7-1.95	.5075	.5015	.4935	.4875	.433	1 1/2	1450	163.82	